WALL WASH 12V COLOR CHANGING

5021-CCBBR



LANDSCAPE LIGHTING



Fixture Type:
Catalog Number:
Project:
Location:

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- Color and brightness are controlled through ilumenight app
- Solid diecast brass
- A uniform wide distribution wall wash from a small form factor
- IP66 rated, Protected against high-pressure water jets
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

	Color Temp	Finish
5021 Wall wash 12V	CC Color Changing	BBR Bronze on Brass

SPECIFICATIONS

Input: 9V - 15VAC (Transformer is required)
Power: 0.5W to 14.5W / 1VA to 17VA

Brightness: Up to 430 lm

Beam Angle: 15° upward (50° by 80°)

CRI: 95+ **Rated Life**: 45,000 hours

Controls: Bluetooth v4.0 - Configured with ilumenight™ iOS

App for localized

(within 150ft line of sight) groups of 8 luminaires or

ess.

Control detection can be adversely affected high wireless signal interference environments.

5021-CCBBR

WALL WASH 12V COLOR CHANGING





Accessories					
Additional Stake	9000-ST9-BK	9000-ST9-BK			Durable PC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR			n	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ	5000-GM-BZ			Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ	5000-TCP-BZ Bronze on Aluminum		m	Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes
Optics	LENS-2X4-AMB LENS-2X4-GRN LENS-2X4-RED	Amber Green Red	LENS-2X4-BLU LENS-2X4-FR LENS-2X4-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 5000-X08-BZ 5000-X12-BZ	4 in 8 in 12 in	5000-X18-BZ 5000-X24-BZ	18 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

