## 1" INGROUND - SQUARE


1051



### LANDSCAPE LIGHTING







Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### PRODUCT DESCRIPTION

Landscape 1" recessed inground luminaire for up, down, side light applications.

#### **FEATURES**

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

#### **ORDERING NUMBER**

	Color	Гетр	Finish	
<b>1051</b> Square	30	3000K	ss	Stainless Steel

1051-30SS

**SPECIFICATIONS** 

**Input:** 9 - 15VAC (Transformer is required)

Power: 1.9W / 3VA Brightness: 80 lm Beam Angle: 50° CRI: 85

Rated Life: 70,000 hours

# 1" INGROUND - SQUARE

1051



### **Magnetic Transformers**



Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

9150-TRN-SS 150W Max **9300-TRN-SS** 300W Max

**9600-TRN-SS** 600W Max

1" Concrete Pour Adapter



For installation in concrete. Use with a 4" outdoor rated junction box and a trade size 1" schedule 80 PVC pipe

1000-CON-PVC

#### **TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS**

Luminaire	Dimmer							
	Manufacturer	Family	Model	Power Rating	Range*	Note		
		Diva	DVLV-600	600W	28% - 100%	Output maxes at 70% dimming level		
1051	Lutron	Skylark	SLV-600P	600W	20% - 100%	Output maxes at 70% dimming level		
		Skylark	S-10P	1000W		Not recommended		

<sup>\*</sup>Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.