




## LANDSCAPE LIGHTING







Fixture Type:	
Catalog Number	:
Project:	

### PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for soft ground application.

#### **FEATURES**

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

### **ORDERING NUMBER**

		Colo	Color Temp		
2011	Slim round	30	3000K	BS SS	Bronzed Stainless Steel Stainless Steel

<b>SPECIFICATIO</b>	NS

Location:

9 - 15VAC (Transformer is required)

4.1W / 6.6VA Power: Brightness: 170 lm Beam Angle: 25° CRI: 85

Rated Life: 70,000 hours

IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and shear loads test	N/A	Yes

2011-30\_\_\_\_

Example: 2011-30SS





### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

**9150-TRN-SS** *150W Max* 

**9300-TRN-SS** *300W Max* 

**9600-TRN-SS** 600W Max



#### **TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS**

Luminaire	Dimmer						
	Manufacturer	Family	Model	Power Rating	Range*	Note	
		Diva	DVLV-600	600W	20% - 100%		
2011	Lutron	Skylark	SLV-600P	600W	15% - 100%	Best performance	
		Skylark	S-10P	1000W		Not recommended	

<sup>\*</sup>Low end of this range is determined by output current which may not directly translate to the perceived light output


WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.



## 2012 Honeycomb louver

### LANDSCAPE LIGHTING





### PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for soft ground application.

#### **FEATURES**

- Integrated honeycomb louver for glare reduction
- 30° visual cutoff
- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

#### **SPECIFICATIONS**

**Input:** 9 - 15VAC (Transformer is required)

Power: 4.1W / 6.6VA
Brightness: 155lm
Beam Angle: 25°
CRI: 85

Rated Life: 70,000 hours


#### **ORDERING NUMBER**

	Color Temp		Finish	
2012 Slim round Honeycomb louver	30	3000K	BS SS	Bronzed Stainless Steel Stainless Steel

IEC safety Standard	Walk over	Drive over	
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)	
Resistance to torque and shear loads test	N/A	Yes	

2012-30

Example: 2012-30SS



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760





### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

**9150-TRN-SS** *150W Max* 

**9300-TRN-SS** 300W Max

**9600-TRN-SS** 600W Max



#### **TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS**

Luminaire	Dimmer						
Luminaire	Manufacturer	Family	Model	Power Rating	Range*	Note	
2012 Lutron		Diva	DVLV-600	600W	20% - 100%		
	Lutron	Skylark	SLV-600P	600W	15% - 100%	Best performance	
		Skylark	S-10P	1000W		Not recommended	

<sup>\*</sup>Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.