





Fixture Type:				
Catalog Number:				
Project:				
Location:				

PRODUCT DESCRIPTION

Landscape mini accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Continuously Adjustable Beam Angles. Indexed at 10°, 25°, 40°, 50°
- Continuously Adjustable brightness control. Indexed at 1W, 2W, 4W, 6W, 7W
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Constant output for 9V-15V input
- Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included
- MLV dimmable with remote MLV dimmers

SPECIFICATIONS

Input: 9 -15VAC

Power: 1W to 7W / 2VA -10.5VA **Brightness:** 45 lm to 365 lm

Beam Angle: 10° to 50° **CRI:** 85

Rated Life: 70,000 hours

ORDERING NUMBER

	Colo	r Temp	Finish	
5111 Mini Accent 1	2V 27 30	2700K Warm White 3000K Pure White	BK BZ BBR WT	Black on Aluminum Bronze on Aluminum Bronze on Brass White on Aluminum

5111-30

Example: 5111-30BBR

MINI ACCENT 12V

5111



Accessories						
Accent Snoot	5111-SNOOT-BK 5111-SNOOT-BZ 5111-SNOOT-BBR		Black on Aluminum Bronze on Aluminum Bronze on Brass		Shields lamp and reduces glare	
5" Long Shroud	5111-LSHR-BK 5111-LSHR-BZ 5111-LSHR-BBR		Black on Aluminum Bronze on Aluminum Bronze on Brass		Reduce glare. Ideal for downlighting application	
Additional Stake	9000-ST9-BZ		Bronze		Durable PVC stake	
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK		Bronze on Aluminum Bronze on Brass Black on Aluminum		Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box	
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal	
Gutter Mount Bracket	5000-GM-BZ 5000-GM-Bk		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture	
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminum Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes	
Optics	LENS-16-AMB LENS-16-GRN LENS-16-RED LENS-16-BLU	Amber Green Red Blue	LENS-16-FR LENS-16-SPR LENS-16-BEL	Frosted Spread Elongating	Enhances saturation of florals and foliage	
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X08-BZ 5000-X08-BK 5000-X12-BZ 5000-X12-BK	4 in 4 in 8 in 8 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box	
Rod L-Coupler	5000-LCO-BZ		Bronze			

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max

