GRAND ACCENT 120V



LANDSCAPE LIGHTING

		Fixture Type:	
		Catalog Numbe	r:
		Project:	
Cr.		Location:	
	Ø39%6 81/4	734"	

PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 Listed
- Not suitable to use with external dimmers

ORDERING NUMBER

	Color Temp	Finish
5212 Grand Accent 120V	30 3000K 40 4000K	BK Black on Aluminum BZ Bronze on Aluminum BBR Bronze on Brass

5212-____

Example: 5212-40BK

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

SPECIFICATIONS

Input:	110V - 120VAC
Power:	13W to 31W. 70lm/W
Brightness:	780lm - 2150lm
Beam Angle:	15° to 60°
CRI:	85+
Rated Life:	45,000 hours

5212

GRAND ACCENT 120V

5212



LANDSCAPE LIGHTING

Accessories

5211-SNOOT-BK 5211-SNOOT-BZ 5211-SNOOT-BBR	Black on Aluminum Bronze on Aluminum Bronze in Brass	Shields lamp and reduces glare
5211-LSHR-BZ 5211-LSHR-BK 5211-LSHR-BBR	Black on Aluminum Bronze on Aluminum Bronze in Brass	Reduce glare. Ideal for downlighting application
M6000-STAKE	PVC	<i>Easy wiring accessory designed for 12V & 120V products.</i> <i>Eliminates the need for a separate Junction box.</i>
5000-TCP-BZ	Bronze on Aluminum	Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ "NPT threaded holes
LENS-25-AMB Amber LENS-25-GRN Green LENS-25-RED Red	LENS-25-BLU Blue LENS-25-FR Frosted	Enhances saturation of florals and foliage
5000-X04-BZ 4 in 5000-X08-BZ 8 in 5000-X12-BZ 12 in	5000-X18-BZ 18 in 5000-X24-BZ 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
5000-LCO-BZ	Bronze	
	5211-SNOOT-BZ 5211-SNOOT-BBR5211-LSHR-BZ 5211-LSHR-BBR5211-LSHR-BK 5211-LSHR-BBRM6000-STAKE5000-TCP-BZLENS-25-AMB LENS-25-REDAmber Green Red5000-X04-BZ 5000-X08-BZ 5000-X12-BZ4 in 8 in 12 in	5211-SNOOT-BZ 5211-SNOOT-BBRBronze on Aluminum Bronze in Brass5211-LSHR-BZ 5211-LSHR-BK 5211-LSHR-BBRBlack on Aluminum Bronze on Aluminum Bronze on Aluminum Bronze in BrassM6000-STAKEPVC5000-TCP-BZBronze on Aluminum Bronze on Aluminum Bronze on Aluminum Bronze in BrassLENS-25-AMB LENS-25-REDAmber Green Red5000-X04-BZ 5000-X12-BZ4 in 8 in 12 in

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max **9150-TRN-SS** 150W Max **9300-TRN-SS** *300W Max* **9600-TRN-SS** 600W Max



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 17 2018