# **CANOPY** LED AREA LIGHT





# LANDSCAPE LIGHTING



Fixture Type:		
Catalog Numbe	r:	
Project:		
Location:		

#### **PRODUCT DESCRIPTION**

Sturdy side mount design works well in applications where directional illumination is desired

### **SPECIFICATIONS**

**Input:** 9-15VAC (Transformer is required)

 Power:
 6.5W / 9.5VA


 Brightness:
 Up to 225 lm

 CRI<sup>↑</sup>
 90+

 Rated Life:
 60,000 hours

### **FEATURES**

- IP66 rated, Protected against powerful water jets
- Factory sealed water tight fixtures
- Solid brass or corrosion resistant aluminum alloy
- Recommended spacing for installation: Residential: 7 to 9ft; Commercial: 5 to 7ft
- Mounting stake, 6 foot lead wire, and direct burial gel filled wire nuts are included
- Maintains constant lumen output against voltage drop
- UL & cUL 1838 Listed



#### **ORDERING NUMBER**

Color Temp			Finish	Finish	
6051	Canopy	27 30	2700K Warm White 3000K Pure White	BBR BZ BK	Bronze on Brass Bronze on Aluminum Black on Aluminum

6051- BK

Example: 6051-30BK

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

# **CANOPY LED AREA LIGHT**

6051



## Surface Mount Flange/Stake



Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box

Additional Mounting Stake



**9000-ST9-BK** *Durable PVC stake* 





### **Guardian Mount**

Heavy duty stainless steel spike to position fixture. Formed from a single piece of metal

**9000-SP9-BZ**Stainless Steel

## Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

**9150-TRN-SS** *150W Max* 

**9300-TRN-SS** *300W Max* 

**9600-TRN-SS** 600W Max

