
## **SLIDE** LED PATH LIGHT





### LANDSCAPE LIGHTING





Fixture Type:	
Catalog Number:	
Project:	

#### PRODUCT DESCRIPTION

Sleek linear design blends seamlessly into pathways while providing soft, even illumination

## SPECIFICATIONS

Location:

**Input:** 9-15VAC (Transformer is required)

 Power:
 3.0W / 4.5VA


 Brightness:
 Up to 95 lm

 CRI:
 90

 Rated Life:
 60,000 hours

#### **FEATURES**

- · IP66 rated, Protected against powerful water jets
- · Factory sealed water tight fixtures
- Translucent lens provides uniform light distribution
- Constant output for 9V-15V input
- Mounting stake, 6 foot lead wire, and direct burial gel filled wire nuts are included
- Recommended spacing for installation: Residential: 7 to 9ft; Commercial: 4 to 6ft
- Maintains constant lumen output against voltage drop
- UL & cUL 1838 Listed (12V)



#### **ORDERING NUMBER**

	Color Temp	Finish
<b>6311</b> Small SI	de 30 3000K Pure Whit	te <b>BZ</b> Bronze on Aluminum

6311- BZ

Example: **6311-30BZ** 



#### Surface Mount Flange/Stake



Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box

# **5000-SCP-BZ**Bronze on Aluminum

Additional Mounting Stake



**9000-ST9-BK** *Durable PVC stake* 



#### **Guardian Mount**

Heavy duty stainless steel spike to position fixture. Formed from a single piece of metal

**9000-SP9-BZ** *Stainless Steel* 

#### Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** *75W Max* 

**9150-TRN-SS** *150W Max* 

**9300-TRN-SS** 300W Max

**9600-TRN-SS** 600W Max

