INTERBEAM ACCENT 12V

5311



LANDSCAPE LIGHTING



Fixture Type:	
Catalog Numbe	er:
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape Interbeam accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Continuously Adjustable Beam Angles. Indexed at 20°, 35°, 60°
- IP66 rated, Protected against high-pressure water jets
- Corrosion resistant aluminum
- · Factory sealed water tight fixtures
- Constant output for 9V-15V input
- · Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included
- MLV dimmable with remote MLV dimmers

SPECIFICATIONS

Input: 9-15VAC Power: 6W / 7.7VA **Brightness:** 475 lm **Beam Angle:** 20° to 60° CRI: 85 Rated Life:

70,000 hours

ORDERING NUMBER

	Color Temp	Finish
5311 12V	27 2700K Warm White30 3000K Pure White	BK Black on Aluminum BZ Bronze on Aluminum

5311-30

Example: **5311-30BZ**

INTERBEAM ACCENT 12V





Accessories					
Accent Snoot	5111-SNOOT-BK 5111-SNOOT-BZ		Black on Aluminum Bronze on Aluminum		Shields lamp and reduces glare
5" Long Shroud	5111-LSHR-BK 5111-LSHR-BZ		Black on Aluminum Bronze on Aluminum		Reduce glare. Ideal for downlighting application
Additional Stake	9000-ST9-BZ		Bronze		Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BK		Bronze on Aluminum Black on Aluminum		Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ 5000-GM-Bk		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-TCP-BZ 5000-TCP-BK		Bronze on Aluminum Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes
Optics	LENS-16-GRN (Amber Green Red Blue	LENS-16-FR LENS-16-SPR LENS-16-BEL	Frosted Spread Elongating	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BK	4 in 4 in 8in 8 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ		Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max

