INTERBEAM ACCENT 12V

5411




LANDSCAPE LIGHTING



Fixture Type:		
Catalog Number:		

Location:

Project:



PRODUCT DESCRIPTION

Landscape Interbeam accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Continuously Adjustable Beam Angles. Indexed at 20°, 35°, 60°
- IP66 rated, Protected against high-pressure water jets
- Corrosion resistant aluminum
- Factory sealed water tight fixtures
- Constant output for 9V-15V input
- Can be used as an uplight or downlight
- 2700K or 3000K color temperature
- Mounting stake, detachable shroud, 6' lead wire and direct burial gel filled wire nuts included
- · MLV dimmable with remote MLV dimmers

SPECIFICATIONS

 Input:
 9 - 15 VAC

 Power:
 3W / 5.5 VA

 Brightness:
 245 lm

 Beam Angle:
 20° to 60°

 CRI:
 85

 Rated Life:
 70,000 hours

ORDERING NUMBER

		Color Temp			Finish		
5411	12V	27 30	2700K Warm White 3000K Pure White	BK BZ	Black on Aluminum Bronze on Aluminum		

5411-30____

Example: **5411-30BZ**

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

INTERBEAM ACCENT 12V

5411



LANDSCAPE LIGHTING

Accessories

Accent Snoot	5111-SNOOT-BK 5111-SNOOT-BZ	Black on Aluminum Bronze on Aluminum		Shields lamp and reduces glare
5" Long Shroud	5111-LSHR-BK 5111-LSHR-BZ	Black on Aluminum Bronze on Aluminum		Reduce glare. Ideal for downlighting application
Additional Stake	9000-ST9-BZ	Bronze		Durable PVC stake
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BK	Bronze on Aluminum Black on Aluminum		Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box
Guardian Mount	9000-SP9-BZ	Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal
Gutter Mount Bracket	5000-GM-BZ 5000-GM-Bk	Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture
Tree Mount Junction Box	5000-ТСР-ВZ 5000-ТСР-ВК	Bronze on Aluminum Black on Aluminum	tainless Steel	Bronze on Aluminum box with Stainless steel mounting screws. Two 2" NPT threaded holes
Optics	LENS-16-AMB Amb LENS-16-GRN Green LENS-16-RED Red LENS-16-BLU Blue	I FNS-16-FR	Frosted Spread Elongating	Enhances saturation of florals and foliage
Extension Rods	5000-X04-BZ 4 in 5000-X04-BK 4 in 5000-X08-BZ 8in 5000-X08-BK 8in 5000-X12-BZ 12 in 5000-X12-BK 12 in	5000-X18-BZ 5000-X18-BK 5000-X24-BZ 5000-X24-BK	18 in 18 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
Rod L-Coupler	5000-LCO-BZ	Bronze		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS 150W Max

9300-TRN-SS *300W Max*

9600-TRN-SS 600W Max

